



Начало — на предыдущей странице.

Вал Диам. d		Обозначение фланца с четырьмя болтами	Обозначение подшипника	Базовая грузоподъемность		Размеры									Размер болта	Масса
				Динамическая	Статическая	L	J	A <sub>1</sub>	A	A <sub>0</sub>	S	B	A <sub>2</sub>	N		
				C <sub>r</sub>	C <sub>0r</sub>											
мм	дюймы				мм	мм	мм	мм	мм	мм	мм	мм	мм	мм	мм	кг
50	1 7/8	UCF210-30	UC210-30	35,1 7891	23,3 5238	143 5 5/8	111 4 3/8	16 5/8	40 1 1/8	54,6 2 1/2	19,0 0,748	51,6 2,031	22 5/8	16 5/8	M14 1/2	2,5 5,5
	1 5/16	UCF210-31	UC210-31													
		UCF210	UC210													
	2	UCF210-32	UC210-32													
55	2	UCF211-32	UC211-32	43,4 9757	29,4 6609	162 6 3/8	130 5 1/8	18 29/32	43 1 11/16	58,4 2 19/64	22,2 0,874	55,6 2,189	25 63/64	19 3/4	M16 5/8	3,4 7,5
	2 1/8	UCF211-34	UC211-34													
		UCF211	UC211													
	2 3/16	UCF211-35	UC211-35													
60	2 1/4	UCF212-36	UC212-36	52,4 11780	36,2 8138	175 6 7/8	143 5 5/8	18 29/32	48 1 7/8	68,7 2 45/64	25,4 1,000	65,1 2,563	29 1 1/4	19 3/4	M16 5/8	4,2 9,3
		UCF212	UC212													
	2 3/8	UCF212-38	UC212-38													
	2 7/16	UCF212-39	UC212-39													
65	2 1/2	UCF213-40	UC213-40	57,2 12859	40,1 9015	187 7 3/8	149 5 59/64	22 7/8	50 1 31/32	69,7 2 3/4	25,4 1,000	65,1 2,563	30 1 3/16	19 3/4	M16 5/8	5,2 11,5
		UCF213	UC213													
	2 3/4	UCF214-44	UC214-44													
		UCF214	UC214													
70	2 5/8	UCF215-47	UC215-47	62,2 13983	44,1 9914	193 7 19/32	152 5 63/64	22 7/8	54 2 1/8	75,4 2 31/32	30,2 1,189	74,6 2,937	31 1 7/32	19 3/4	M16 5/8	5,9 13,0
		UCF215	UC215													
	3	UCF215-48	UC215-48													
		UCF216	UC216													
75	3 1/8	UCF216-50	UC216-50	72,7 16344	53,0 11915	208 8 3/16	165 6 1/2	22 7/8	58 2 1/2	83,3 3 3/32	33,3 1,311	82,6 3,252	34 1 11/32	23 29/32	M20 3/4	7,3 16,1
		UCF217	UC217													
	3 1/4	UCF217-52	UC217-52													
		UCF218	UC218													
80	3 1/4	UCF217-52	UC217-52	84,0 18884	61,9 13916	220 8 21/32	175 6 57/64	24 1 5/16	63 2 15/32	87,6 3 29/64	34,1 1,343	85,7 3,374	36 1 27/64	23 29/32	M20 3/4	8,9 19,6
		UCF218	UC218													
	3 1/2	UCF218-56	UC218-56													
		UCF218	UC218													
85	3 1/2	UCF218-56	UC218-56	96,1 21604	71,5 16074	235 9 1/4	187 7 23/64	25 31/32	68 2 11/16	96,3 3 25/32	39,7 1,563	96,0 3,780	40 1 37/64	23 29/32	M20 3/4	11,4 25,1
		UCF218	UC218													